

GR 29 U/W, Hydraulic Grinder

Description:

The Stanley Hydraulic GR29 Grinder is a right angle grinder ("vertical grinder") that can be used for grinding and cleaning in underwater applications with a variety of wheels, brushes and attachments. The high torque gear motor drives a standard 5/8 - 11 inch threaded spindle. A 9 inch adjustable wheel guard, two position assist handles and a trigger guard are standard.

Features:

- Integral Stanley Hyrevz gear motor produces high torque
- Stainless Steel spools and fasteners
- Two position assist handle for right/left hand operation
- Oversized trigger with guard for diver comfort
- Adjustable wheel guard for infinite positions
- Plastisol covered handle for comfortable ergonomic grip

- Use with grinding wheels, hull scrubbing brushes, wire and nylon brushes, barnacle busters and Desmond wheels
- 3200RPM @ 12gpm
- Cast-in lifting eye
- Painted hi-visibility yellow

Specifications:

Capacity: 9" / 23cm Wheel
 Spindle: 5/8" – 11" Threaded
 Circuit Type: Open Center
 Flow Range: 4-12gpm / 15-45lpm
 Working Pressure: 1000 - 2000psi / 70-140bar
 Full Relief Setting: 2250psi / 155bar
 RPM: 3200 @ 12gpm / 45lpm
 Weight (with guard): 15lbs / 6.8kg
 Length: 11" / 28cm
 Width (with guard): 10¼" / 26cm
 Hydraulic Ports: -8 SAE O-ring
 Connection Size and Type: 3/8" Male Pipe Adapter
 Hose Whips: No



Order Detail:

Hydraulic Grinding Tool - Stanley Tool u/w, 9in capacity, GR 29 U/W	D-ST-162
---	----------