

HPP 300E, Electric Hydraulic Tool HPU

Description:

The HPP 300E is hydraulic tool power unit that features a vertically mounted 30kW electric motor. The power pack features variable hydraulic flow rate of up to 55 litres per minute which makes it suitable to run virtually any form of hand held hydraulic tool including the complete range of Stanley hydraulic hand tools.

Features:

- Pressure compensated flow control valve for variable hydraulic flow
- 4-purpose built lifting points and 4 – point lifting sling
- Shell and tube water heat exchanger
- 250L oil tank capacity
- Variable flow axial piston pump
- an Hour meter on the control box
- Low-oil level cut out

Specification:

Electric Motor Power: 30kW @1750RPM
 Frequency: 60Hz
 Operating Voltage: 440Volts
 IP Rating (motor and panel): IP56
 Adjustable pressure: 2-28MPa
 Max. relief pressure setting: 30MPa
 Oil flow rate from hydraulic pump: 5-55l/min @ 60Hz
 Oil reservoir capacity: 250L
 Oil Type: ISO VG 46
 Sea Water Cooler: 15kW heat dissipation capacity at specified flow
 Required sea water flow: 30l/min
 Max. water flow: 45l/min
 Lifting lugs SW:L: 1000kg
 Filtration: 10µ tank top with clogging indicator



Order Detail:

HPU 300-E Electric Hydraulic Tool HPU	D-ST-266
Spares for HPU 300E	D-ST-266-01